

Tech Data: Custom Laminate

Options
Personalized Laminate Suppliers <ul style="list-style-type: none">WilsonartFormicaPionite
Image Types <ul style="list-style-type: none">PhotosDrawingsGraphic designsTextLogos

Personalized Laminate

Custom printed, high pressure laminate 0.039 inch (0.991 mm) thick is bonded under pressure with an environmentally friendly, PVA-type adhesive to 45 pound, industrial-grade particle board. All edges are self-edged.

Doors and Panels

Doors and panels made with personalized laminate are 7/8" thick (typical).

Pilasters

Personalized laminate pilasters are 1-1/4" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

Considerations

- Not guaranteed in wet areas.
- Sample approval time is in addition to manufacturing lead times.
- File formats and transfer methods vary by supplier.
- Full sheet indexing is not available.
- Permission to use images and graphics are required.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.