

Tech Data: Inlays

Options

Inlay Materials and Designs

- Wood Veneer
- Decorative Metals
- Plastic laminate (HPL)
- Can be most standard geometric shapes
- Minimum 6" wide and 6" tall inlay design(s)

Inlays

Materials are cut to within 0.001" tolerance of the specified design. Inlays are not water-tight. Inlays are attached to doors and panels with environmentally friendly adhesives and have no visible gaps.

Doors and Panels

Inlaid doors and panels made with a variety of materials and material combinations.

Pilasters

Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

Considerations

- Design complexity will likely impact lead time.
- Best results are realized using same-thickness materials.
- Inlay doors are not guaranteed in wet areas.
- Complex designs should consider using personalized laminate.

4/11/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.