

Tech Data: Phenolic

| Options | |
|---|---|
| Phenolic Suppliers | |
| <ul style="list-style-type: none">• Wilsonart• Formica• Nevamar• Pionite | <ul style="list-style-type: none">• Laminart• Abet Laminati• More ... |
| Finishes | |
| <ul style="list-style-type: none">• Standard matte• High gloss• Textured | <ul style="list-style-type: none">• Fire-rated• Custom images |

Phenolic

Sheets of kraft paper impregnated with phenolic resins are heated, pressed. Both faces of the core are covered with a decorative sheet and a transparent melamine overlay that provides wear protection and surface finish.

Pilasters

Phenolic pilasters are 3/4" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

Considerations

- All edges are black.
- Material should be stored flat.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.