

# Tech Data: Stone

Options	
<b>Stone Materials and Suppliers</b>	
<ul style="list-style-type: none"><li>• Granite</li><li>• Marble</li><li>• Onyx</li></ul>	<ul style="list-style-type: none"><li>• Engineered Quartz</li><li>• Stoneply</li><li>• Silestone</li></ul>
<b>Stone Finishes</b>	
<ul style="list-style-type: none"><li>• Polished reflective</li><li>• Polished non-reflective</li><li>• Rough granite</li></ul>	<ul style="list-style-type: none"><li>• Fractured texture</li><li>• Rugged</li><li>• Grooved</li></ul>

## Stone

0.25" thick natural or engineered stone bonded under pressure to 0.50" thick. Aluminum honeycomb core.

## Doors and Panels

Doors and panels made with stone are 1/2" thick (typical).

## Pilasters

Stone pilasters are 1/2" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

## Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

## Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

## Considerations

- Stone colors and "grains" may vary significantly piece to piece.
- Material availability may affect lead times.
- Installation may require significant time and specialized tools.
- Abrasive cleaning solutions are not appropriate for stone.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.