

Tech Data: Stone

Options
Stone Materials and Suppliers <ul style="list-style-type: none">• Granite• Marble• Onyx• Engineered Quartz• Stoneply• Silestone
Stone Finishes <ul style="list-style-type: none">• Polished reflective• Polished non-reflective• Rough granite• Fractured texture• Rugged• Grooved

Stone

0.25" thick natural or engineered stone bonded under pressure to 0.50" thick. Aluminum honeycomb core.

Doors and Panels

Doors and panels made with stone are 1/2" thick (typical).

Pilasters

Stone pilasters are 1/2" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

Considerations

- Stone colors and "grains" may vary significantly piece to piece.
- Material availability may affect lead times.
- Installation may require significant time and specialized tools.
- Abrasive cleaning solutions are not appropriate for stone.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.