

Tech Data: Wood Veneer

Options	
Wood Species	
<ul style="list-style-type: none">• Alder• Birch• Cherry• Mahogany	<ul style="list-style-type: none">• Maple• Red or White Oak• Walnut• More ...
Wood Finishes	
<ul style="list-style-type: none">• Paint to match sample• Stain to match sample	<ul style="list-style-type: none">• Clear coat• Unfinished

Wood Veneer

Consist of 0.037" (typical) wood veneer bonded under pressure with environmentally friendly, PVA type adhesive to 45 pound, industrial-grade particle board. All edges are banded with a slightly thicker veneer of the same species.

Doors and Panels

Doors and panels made with wood veneer are 7/8" thick (typical).

Pilasters

Wood veneer pilasters are 1-1/4" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

Considerations

- Wood veneer not guaranteed in wet areas.
- Many cleaning solutions are not appropriate for real wood.
- Wood colors and grains may vary from log to log.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.

