

# Tech Data: Laminate

Options	
Plastic Laminate Suppliers	
<ul style="list-style-type: none"><li>• Wilsonart</li><li>• Formica</li><li>• Nevamar</li><li>• Pionite</li></ul>	<ul style="list-style-type: none"><li>• Laminart</li><li>• Abet Laminati</li><li>• More ...</li></ul>
Finishes	
<ul style="list-style-type: none"><li>• Standard matte</li><li>• High gloss</li><li>• Textured</li></ul>	<ul style="list-style-type: none"><li>• Fire-rated</li><li>• Custom images</li></ul>

## Laminate (HPL)

High pressure laminate 0.039 inch (0.991 mm) thick is bonded under pressure with an environmentally friendly, PVA-type adhesive to 45 pound, industrial-grade particle board. All edges are self-edged.

## Doors and Panels

Doors and panels made with laminate are 7/8" thick (typical).

## Pilasters

Laminate pilasters are 1-1/4" thick (typical). Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

## Door Hardware

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

## Brackets

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

## Considerations

- Not guaranteed in wet areas.
- Material availability may affect lead times.
- Proper consideration should be given to cleaning requirements.
- Components over 48" may require splices.
- Job site handling should be minimized.

4/12/2014

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all rough-in dimensions prior to installation.