



CEILING HUNG STYLE

This style is mounted to the ceiling and is recommended where complete floor access is desired. Requires pre-installed structural ceiling support and is not recommended for ceiling heights over 8'.

PILASTERS

The ceiling edge of the pilaster shall be provided with a mechanically fastened 3/8" steel leveling bar. Pilasters are attached to the ceiling using 3/8" threaded rod, hex nuts, and washers to provide vertical and horizontal adjustments. Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

DOOR HARDWARE

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

BRACKETS

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

CONSIDERATIONS

- Ceiling hung systems will likely require ongoing adjustments to perform properly.
- Structural steel must be set within 2" of pilaster connection
- Pedestals may be added to provide additional stability.

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all roughin dimensions prior to installation.
