

DESCRIPTION

Options

Personalized Laminate Suppliers

- Wilsonart

Image Types

- Photos
- Drawings
- Graphic Designs
- Text
- Logos

PERSONALIZED LAMINATE (HPL)

Custom printed, high pressure laminate 0.039 inch (0.991 mm) thick is bonded under pressure with an environmentally friendly, PVA-type adhesive to 45 pound, industrial-grade particle board. All edges are edgebanded.

DOORS & PILASTERS

Laminate Doors and Pilasters are 1-1/4" thick (typical). Shoes are 22 gauge, ASTM A167 stainless steel with satin finish, not less than 3" in height.

PANELS

Laminate panels are 7/8" thick (typical).

DOOR HARDWARE

Hinges are surface mount and through bolted, strikes/keepers are a slide Indicator latch (typical). Coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

BRACKETS

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners (typical).

CONSIDERATIONS

- Not guaranteed in wet areas.
- Sample approval time in addition to manufacturing lead times.
- Required file formats and transfer methods vary by manufacturer.
- Full sheet indexing is not available.
- Permission to use images and graphics is required.
- Proper consideration should be given to cleaning requirements.
- Job site handling should be minimized.