

DESCRIPTION

Door Lite doors are constructed from stile and rails and a recessed acrylic panel. Components are assembled using dowels and adhesive. Stiles are machined to accept the lite including a rubber backer to absorb expansion and contraction and reduce rattling of the door assembly.

CONSIDERATIONS

Doors may require additional cleaning care and time due to dissimilar materials and additional inside angles.

Wet area applications require appropriate material selection.

Door Lite doors not recommended for high abuse areas.

Lite insert selection is required. Chart is located on website.

CONSTRUCTION

Stiles: 5 1/8" wide and vary in thickness by material.

Top rail: 5 1/8" tall and vary in thickness by material.

Bottom rail: 7 1/2" tall and vary in thickness by material.

Lite: 3/8" thick by 1" wider and taller than opening.

Assembly: stiles and rails are assembled using dowels and epoxy adhesive. The lite is friction fit with a rubber anti-vibration unit included.

DIMENSIONS

Stile and Rail Thickness		
Material	inch	mm
High Pressure Laminate	1 1/4"	32
Wood Veneer	1 1/4"	32
Compact Laminate	1"	25

Available Door Width	
inch	mm
24"	610
34"	864
36"	914

Available Door Height	
inch	mm
58"	1473
72"	1829
84"	2134

