

DESCRIPTION

Options

Inlay Materials and Designs

- Wood Veneer
- Decorative Metals
- Plastic laminate (HPL)
- Can be most standard geometric shapes
- Minimum 6" wide and 6" tall inlay design(s)

INLAYS

Materials are cut to within 0.001" tolerance of the specified design. Inlays are not water-tight. Inlays are attached to doors and panels with environmentally friendly adhesives and have no visible gaps

DOORS & PANELS

Inlaid doors and panels made with a variety of materials and material combinations.

PILASTERS

Shoes are 22 gauge ASTM A-167 stainless steel with satin finish, not less than 3" in height.

DOOR HARDWARE

Hinges are surface mount and strikes/keepers are wraparound style. Slide latches, coat hooks, and bumpers are surface mounted. Door pulls are through bolted. All fasteners are tamper proof.

BRACKETS

Stirrup-type one ear, two-ear, and u-brackets are provided with theft resistant fasteners.

CONSIDERATIONS

- Design complexity will likely impact lead time.
- Best results are realized using same-thickness materials.
- Inlay doors are not guaranteed in wet areas.
- Complex designs should consider using personalized laminate.

Ironwood Manufacturing reserves the right to make changes in design, material, and documentation without formal notice and without incurring obligation. Consult local and national codes: conformity and compliance to local and national codes is the responsibility of the installer. Verify all roughin dimensions prior to installation.
